

Lenovo ThinkVision T34WD-40 Monitor

Catapults your productivity to a whole new level.




Striking visual clarity and savings

Variable refresh rate<sup>1</sup> screen technology adapts to different workflows for optimized visual smoothness. The monitor can automatically reduce the refresh rate from 120Hz to 48Hz for less demanding content, saving more power in the long run.



Exceptional productivity, intelligent docking

Immerse yourself in work and maximize your productivity on this monitor with its large 34-inch screen size and 1500R curvature. Collaborate with your colleagues easily with the wide viewing angles of the VA panel. Power up work devices at full throttle with 100W PD 3.0<sup>2</sup> on ThinkVision T34WD-40 monitors.



Supremely efficient asset management

Manage and control your monitor assets with Lenovo Display Fleet Manager (LDFM). This innovative software solution empowers IT managers with robust tools for rapid and streamlined asset management, efficient firmware upgrades, and centralized settings control.

## Lenovo ThinkVision T34WD-40 Monitor

### Display

**Panel Size**  
34-inch

**Screen Dimensions**  
801.1 mm x 351.0 mm

**Panel Type**  
4-sided Ultra Thin,  
VA

**Active Area**  
797.2 mm x 333.7 mm

**Curvature**  
1500R

**Backlight**  
WLED

**Aspect Ratio**  
21:9

**Resolution**  
3440 x 1440

**Pixel Pitch**  
0.2318 mm x 0.2318 mm

**Dot/Pixel Per Inch  
(DPI/PPI)**  
110

**Viewing Angle  
(H x V @ CR 10:1)**  
178° / 178°

**Response Time (G to G)**  
4ms (Extreme Mode),  
6ms (Normal Mode)

**Refresh Rate**  
48Hz - 120Hz

**Brightness**  
300 cd/m<sup>2</sup>

**Contrast Ratio (Typical)**  
3000:1

**Dynamic Contrast Ratio  
(Typical)**  
3M:1

**Color Gamut  
(Coverage Ratio)**  
99% sRGB (CIE 1931),  
99% BT.709 (CIE 1931)

**Color Support (Typical)**  
16.7 Million

**Color Depth**  
True 8-bit

**HDR Compliance**  
Yes (HDR10)

**Anti-glare**  
Yes

### Connectivity

**Video Signal**  
1 x USB-C<sup>3</sup> (DP 1.4 Alt Mode HBR2)  
1 x HDMI 2.1<sup>4</sup>  
1 x DP 1.4<sup>5</sup> (HBR2)

**Ethernet (RJ45)**  
Yes (1G)

**USB Upstream**  
1 x USB-A (USB 5Gbps / USB 3.2 Gen 1,  
PD 3.0 up to 100W, DP 1.4 Alt Mode HBR2)<sup>6</sup>

**USB Downstream**  
3 x USB-A (USB 5Gbps / USB 3.2 Gen 1,  
1 x BC1.2)<sup>6</sup>  
1 x USB-C (USB 5Gbps / USB 3.2 Gen 1,  
up to 15W PD (data only))<sup>5</sup>

### Multimedia

**Modular Camera/Speaker Support**  
Yes (Optional Support<sup>7</sup>)

### Special Features

**Software**  
LDFM (Lenovo Display Fleet Manager)  
Lenovo ThinkColour (Lenovo Accessories  
and Display Manager)<sup>8</sup>

**Natural Low Blue Light**  
Yes

**Mirrored Power Button**  
Yes

### Power

**Power Consumption (Typ. / Max.)**  
30.0W / 200.0W

**Power Consumption Sleep/Off Mode**  
< 0.5W

**Power Consumption Switch-Off Mode**  
< 0.3W

**ENERGY STAR Power Consumption  
(Pon / E<sub>REC</sub>)**  
25.6W / 82.0kWh

**Power Supply**  
Internal

**Upstream Power Delivery<sup>9</sup>**  
Up to 100W PD3.0<sup>2</sup>

**Smart Power**  
Yes

**Voltage Required**  
AC 100 to 240 V (50-60Hz)

### Mechanical

**Tilt Angle (Front / Back)**  
-5° / 23.5°

**Swivel Angle (Left / Right)**  
-45° / 45°

**Lift (Max. Range)**  
155 mm

**VESA Mount Capability**  
Yes (100 x 100 mm)

**ThinkCentre M Series Tiny Support**  
Yes, by ThinkCentre Tiny  
Mounting Kit<sup>10</sup> (PN: 4XFIR07369)

**Kensington Nano Security Slot**  
Yes (2.5 mm x 6 mm)

**Cable Management**  
Yes

**Bezel Color**  
Eclipse Black

**Bezel Width (Side)**  
2.0 mm

**Bezel Width (Top)**  
2.0 mm

**Bezel Width (Bottom)**  
12.2 mm

### Dimension & Weight

**Size Packed (W x D x H, mm/inch)**  
980.0 x 186.0 x 495.0 mm  
38.58 x 7.32 x 19.49 inches

**Size Unpacked w/ Stand  
(Highest Position)  
(W x D x H, mm/inch)**  
806.1 x 220.0 x 545.4 mm  
31.74 x 8.66 x 21.47 inches

**Size Unpacked w/ Stand  
(Lowest Position)  
(W x D x H, mm/inch)**  
806.1 x 220.0 x 390.4 mm  
31.74 x 8.66 x 15.37 inches

**Size Unpacked w/o Stand  
(Head Only) (W x D x H, mm/inch)**  
806.1 x 114.7 x 356.5 mm  
31.74 x 4.52 x 14.04 inches

**Weight Packed (kg / lbs.)**  
13.7 kg / 30.3 lbs.

**Weight Unpacked (kg / lbs.)**  
9.2 kg / 20.3 lbs.

**Weight (Head Only) (kg / lbs.)**  
6.4 kg / 14.1 lbs.

### What's in the Box

**Monitor with Stand**  
Yes

**Power Cable (Cable Length)**  
1 x Power Cable (1.8 m)

**DP Cable (Cable Length)**  
1 x DP 1.4 Cable (1.8 m)

**USB Cable (Cable Length)**  
1 x USB Type-C to Type-C Gen 1 Cable  
(1.8 m)

**Factory Calibration Report**  
Yes

**Quick Setup Guide**  
Yes

### Certification

**ENERGY STAR Certification**  
Yes

**TCO**  
10

**TCO Edge**  
2.1

**EPEAT**  
Gold

**Volatile Organic Compound  
Certification**  
Yes

**RoHS (2011/65/EU)**  
Yes

**Windows Certification**  
Windows 10, Windows 11

**EU Energy Level Certification**  
Yes (Level-E)

**China Energy Efficiency Standard**  
Tier 2

**TÜV Rheinland<sup>®</sup> Eye Comfort**  
5 Stars

**TÜV Rheinland<sup>®</sup> Low Blue Light  
(Hardware Solution)**  
Yes

**Eyesafe Display Certification**  
Yes (Eyesafe 2.0)



<sup>1</sup> VRR as specified in HDMI 2.1, DRR for Microsoft Windows. | <sup>2</sup> The output rating (100W, 20V/5A) is based on Lenovo's proprietary VDM technology. It is required to connect to products that support Lenovo VDM to reach maximum power output. Actual power output may vary and may be lower. | <sup>3</sup> USB Type-C and USB-C are registered trademarks of USB Implementers Forum. | <sup>4</sup> Supports 3440 x 1440 @ 120Hz as specified in HDMI 2.1. | <sup>5</sup> Supports max. bandwidth 21.6Gbps. | <sup>6</sup> The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1) 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2) 10 Gbit/s; USB4<sup>®</sup> 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps) 20 Gbit/s; USB4<sup>®</sup> 40Gbps (USB 40Gbps) 40 Gbit/s; Thunderbolt™ 3/4: 40 Gbit/s. | <sup>7</sup> Compatible with ThinkVision VoIP Stack MC60 Monitor Webcam and MS30 Monitor Soundbar. | <sup>8</sup> Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS (functions vary across systems). | <sup>9</sup> Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting. | <sup>10</sup> Sold separately. Need to assemble ThinkCentre Tiny mounting kit (PN: 4XFIR07369) to support Tiny PC installation.

© 2025 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, U.S.A., Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, ThinkVision, and ThinkColour are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others. Specifications may vary depending upon region.